

PRODUCTS.


[New product](#)
[Advanced Search](#)
[SMD Series](#)
[Coils&Inductors](#)
[Multilayer](#)
[Application of products](#)
[Packing Spec.](#)

CONTACT

3L Global Co. 2915 Anvil St.
 North Saint Petersburg, FL 33710,
 U.S.A.
 Tel: +1 (727) 343-2679
 Fax: +1 (727) 343-4410
 Email: 3lglobal@worldnet.att.net



NEW PRODUCTS

[more...](#)


BRI Series: BRI 2D/ 3D/ 4D

Features:

New designed terminal for low cost. Low profile and high current.
 Magnetically shielded construction. Ideal for digital equipment and hand phone of new generation.
 RoHS compliant.

SMTPI Series: SMTPI 0603/ 0604/1004/ 1005/1203/1205/1354

Features:

Lowest height and DCR in this package footprint. Shielded construction.
 handles high transient current spikes without saturation. Frequency up to 5MHz.
 Ultra low buzz noise, due to composite construction. RoHS compliant.



SMW Series: SMW 1608 /2012/2015/2518/3218

Features:

SMW-LB series is wound chip inductors that cover customer's wide range module design by wide-line-up shape, standard, low DCR and high electric current series.

SMDV Series: SMD2520V(P)/3225V(P)/4532V(P)

Features:

The product has good heat durability that withstands lead-free compatible reflow soldering conditions.
 SMD2520V/ 3225V/ 4532V are high Q-characteristic achieved in the miniature winding construction.
 SMD2520VP / 3225VP / 4532VP are low Rdc higher current for the power supply line.



ER Series: ER15/ER19

Features:

Low height : 7.9mm Max. High application frequency : up to 900KHz Power rating : up to 250W.
 Wide operating temperature range: -40~130C. Various topologies are available.
 Dielectric strength: Primary to Secondary & core @1800Vdc. All materials are RoHS compliant.
 Customized designs are welcome.

